

DrainProtector

In-Floor and In-Trough screening devices for the effective removal of solids from wastewater



- Cast and machined in 304 Stainless Steel
- Easy to fit/remove stainless steel baskets
- Mandatory fixed screen below basket
- Watermark certificate No. 23056
- WSAA Appraisal Report TWA 1006
- Fitted directly into floors or the underside of troughs
- Floor units have robust, hinged lids
- *Manufactured exclusively for Eco Guardians Pty Ltd for distribution Worldwide*



ecoguardians

sustainability...by design

Floor & Trough Range

| Application | F660 | F1600 | FT660 | FT1600 |
|----------------------------------|---------|---------|-------|--------|
| Basket capacity (cc) | 660 | 1600 | 660 | 1600 |
| Basket perforation diameter (mm) | 3 | 3 | 3 | 3 |
| Fixed screen perforations (mm) | 4 | 4 | 4 | 4 |
| Upper flange (mm) | 150x150 | 250x250 | | |
| Upper flange diameter (mm) | | | 123 | 183 |
| To fit floor waste diameter (mm) | 100 | 150* | 150* | 150* |
| Overall height (mm) | 168 | 173** | 159** | 159** |



*Can be adapted to fit 100 mm waste
**Excluding 100 mm adaptor

F = Floor Range FT = Trough Range



FURTHER INFORMATION

www.ecoguardians.com.au
info@ecoguardians.com.au

Eco Guardians Pty Ltd
90 St Kilda Rd, St Kilda.
Victoria, 3182, Australia

FREE CALL 1300 556 628



WaterMark

ATS 5200.040
Certificate No. 23056