

DrainProtector

In-Floor and In-Trough screening devices for the effective removal of solids from wastewater



- Cast and machined in 304 Stainless Steel
- Easy to fit/remove stainless steel baskets
- Mandatory fixed screen below basket
- Watermark certificate No. 23056
- Fully compliant with WSAA requirements
- Fitted directly into floors or the underside of troughs
- Floor units have robust, hinged lids
- *Manufactured exclusively for Eco Guardians Pty Ltd for distribution Worldwide*

Floor & Trough Range

Application	F660	F1600	FT660	FT1600
Basket capacity (cc)	660	1600	660	1600
Basket perforation diameter (mm)	3	3	3	3
Fixed screen perforations (mm)	4	4	4	4
Upper flange (mm)	150x150	250x250		
Upper flange diameter (mm)			123	183
To fit floor waste diameter (mm)	100	100	150*	150*
Overall height (mm)	168	173	159**	159**



*Can be adapted to fit 100 mm waste
**Excluding 100 mm adaptor

F = Floor Range FT = Trough Range



FURTHER INFORMATION

www.ecoguardians.com.au
info@ecoguardians.com.au

Eco Guardians Pty Ltd
90 St Kilda Rd, St Kilda.
Victoria, 3182, Australia

FREE CALL 1300 556 628



ATS 5200.040
Certificate No. 23056